

Fast, responsive and sophisticated, the KODAK DC280 Digital Camera means business. Start with two-megapixel resolution with enough detail for photo-realistic 8" x 10" prints. The 30 mm to 60 mm lens, with 2X optical/3X digital zoom, is ideal for all kinds of business uses. And the USB interface lets you download your pictures in moments. Finally, consider its intuitive design and responsive performance. You won't waste time learning a new system—the DC280 looks and feels like the cameras you're familiar with. The DC280 lets you capture business images quickly and professionally. And put them to work immediately.

✓ Stunning Two-Megapixel Resolution

Make sales and marketing materials sparkle with detailed, brilliant pictures. Document your work quickly and efficiently. You'll have enough resolution to make sharp, vividly colorful 8" x 10" prints.

✓ Fast And Responsive

Processes data quickly so you won't be left waiting between shots. You'll be more productive and can take advantage of more opportunities.

✓ Familiar, User-Friendly Design

Looks, feels and behaves much like a traditional camera. There's less of a learning curve, so you can put the DC280 to work immediately.

✓ USB Support For Faster Downloads

Less waiting and faster results, with full USB support that lets you download up to 10X faster than serial interfaces.

✓ Easy To Use And Easy To Like

Recognized by industry sources as a top performing digital camera, the DC280 has received numerous awards and rave reviews. *Photo Techniques* listed it as one of the "World's 25 Best Cameras" (#17). Said *PC Magazine* in its November 1999 issue, "The KODAK DC280 camera is perfect for families and SOHO users who want a very easy-to-operate, fast-shooting camera. And it delivers spectacular images." Among the camera's other awards are *PC Magazine's* Editors' Choice (11/16/99) and *CNET* (computers.com) Editors' Choice (11/99).



DC280 Zoom Digital Camera

Kodak

DC280 Zoom Digital Camera

SPECIFICATIONS

CCD Resolution 1901 x 1212 pixels Image Resolution 1760 x 1168 pixels (high), 896 x 592 pixels (standard) Image Quality Best, better, good Settings Image Storage **KODAK Picture Card**

Viewfinder 1.8" TFT color LCD for preview and review, plus real-image optical viewfinder Auto focus 2X true Lens

optical glass zoom Digital 3X digital zoom Enhancement

Lens Focal Length 30 mm to 60 mm equivalent

Focus Distance Regular: 0.5 m to infinity Macro: 0.25 m to 0.5 m

Exposure Auto, or manual override (+/- 2 EV in 0.5-EV increments), automatic white

balance and exposure lock Shutter Speed 1/2 to 1/755 second

Aperture Range Wide: f/3.0 to f/7.6 Tele: f/3.8 to f/9.6

ISO Equivalent 70

File Format

Self-Timer 10 seconds

Tripod Mount Standard Flash Strobe flash (auto,

fill, red-eye, off), range 1.6' (0.5 m) to 9.8' (3.0 m) wide and 1.6' (0.5 m) to 7.9' (2.4 m) tele

JPEG (EXIF)

User Interface Graphical, menu-driven, easy to navigate

Video Out NTSC and PAL (user selectable)

Special Effects B&W mode; sepia mode; borders included;

document mode

USB, serial, PC Card Interface

Power 4 AA batteries (included) or optional AC adapter

5.2" (w) x 2" (d) x 3" (h); Dimensions 133 mm (w) x 52 mm (d)

x 76 mm (h)

Certifications VCCI, CE, FCC Class B. C-Tick, ICES-003 Class B,

CCIB

Weight 0.75 lb (342 g) without

batteries

Warranty One year

Picture Overlay Time/date stamp, borders

SYSTEM REQUIREMENTS

WINDOWS Systems:

- · WINDOWS 95, 98 or NT 4.0 Software (to use USB, must have WINDOWS 98)
- PENTIUM 90 MHz or greater processor
- 16 MB or more of RAM (32 MB of RAM for NT)
- 70 MB of hard disk space available
- · CD-ROM drive for software installation
- 256-color monitor (16-bit color recommended)
- · Available USB port, serial port or PC card reader

MACINTOSH Systems:

- Power MACINTOSH System, MAC OS 7.5.5 or later (to use USB, must have MAC OS 8.5 or later)
- · 32 MB or more of RAM
- 70 MB of hard disk space available
- · CD-ROM drive for software installation
- 256-color monitor (16-bit color recommended)
- · Available USB port, serial port or PC card reader

PACKAGE CONTENTS

- KODAK DC280 Zoom Digital Camera with handstrap and lens cover
- · KODAK Picture Card (COMPACTFLASH standard)
- · 4 AA alkaline batteries
- · 4 AA Ni-MH rechargeable batteries and charger
- · Serial connection for WINDOWS and MACINTOSH Systems
- · USB cable for use with WINDOWS and MACINTOSH Systems
- · Video cable
- Quick setup guide, user's guide, registration cards

CD-ROMs with software, including:

- PHOTODELUXE Software and PAGEMILL Software from Adobe Systems, Inc. (WINDOWS and MACINTOSH)
- ARCSoft PhotoPrinter Software Version 2.0
- · WINDOWS 95, 98 and NT 4.0 Mounter
- TWAIN Acquire Module
- PHOTOSHOP-compatible plug-in
- KODAK Border Transfer Tool

ORDERING INFORMATION/ACCESSORIES

Product Name	CAT No.
DC280 Zoom Digital Camera (US)	893 3707
(Canada)	199 0159
Recommended Accessories	CAT No.
AC Adapter	190 9262
USB Card Reader	876 4714
96 MB Picture Card	135 9454
64 MB Picture Card	140 4169
48 MB Picture Card	142 0629
32 MB Picture Card	180 6900
20 MB Picture Card	146 8628
Premium Camera Bag	809 2710
PCMCIA Card Adapter	156 1596

KODAK Accessories help make this great camera even better. Ask for them today or visit us at www.kodak.com/go/accessories

For more information on this product, check the Internet at www.kodak.com/go/dc280 Or in the U.S. call 1-800-235-6325; in Canada call 1-800-465-6325, ext. 36100.



IC-782R

TAKE PICTURES. FURTHER.™



CAT No. 850 8293